



HiCube 80 Eco, DN 63 ISO-K, MVP 030-3






HiCube 80 Eco, DN 63 ISO-K, MVP 030-3

- Compact high performance pumping station for all high and ultrahigh vacuum applications
- Plug and play solution with HiPace 80 turbopump and multistage diaphragm pump MVP 030-3
- Intermittent mode adapts the pumping station to the process conditions and saves up to 90% energy
- Easy integration of pressure gauges from the accessories

Dimensions



Technical Data	HiCube 80 Eco, DN 63 ISO-K, MVP 030-3
Backing pump	MVP 030-3
Connection flange (in)	DN 63 ISO-K
Connection flange (out)	Silencer, G 1/8"
Cooling method	Air
Final pressure	< 1 · 10 ⁻⁷ hPa < 7.5 · 10 ⁻⁸ Torr < 1 · 10 ⁻⁷ mbar
Final pressure without gas ballast	< 1 · 10 ⁻⁷ hPa < 7.5 · 10 ⁻⁸ Torr < 1 · 10 ⁻⁷ mbar
Fore-vacuum safety valve	No
Mains connection	110 – 240 V AC, 50/60 Hz
Mains connection: frequency (range)	50/60 Hz
Mains connection: power consumption	270 W
Mains connection: voltage	100 – 240 V
Power consumption max.	270 W
Pumping speed backing pump at 50 Hz	1.8 m³/h 1.06 cfm 30 l/min
Pumping speed for N ₂	67 l/s
Sound pressure level	≤50 dB(A)
Turbopump	HiPace 80
Туре	Turbo pumping station
Weight	13.7 kg 30.2 lb

Order number

HiCube 80 Eco

PM S74 200 00

VACUUM SOLUTIONS FROM A SINGLE SOURCE

Pfeiffer Vacuum stands for innovative and custom vacuum solutions worldwide, technological perfection, competent advice and reliable service.

COMPLETE RANGE OF PRODUCTS

From a single component to complex systems: We are the only supplier of vacuum technology that provides a complete product portfolio.

COMPETENCE IN THEORY AND PRACTICE

Benefit from our know-how and our portfolio of training opportunities! We support you with your plant layout and provide first-class on-site service worldwide.

Are you looking for a perfect vacuum solution? Please contact us:

Pfeiffer Vacuum GmbH Headquarters · Germany T +49 6441 802-0 info@pfeiffer-vacuum.de

www.pfeiffer-vacuum.com

